

Nokian Tyres plc

Tyre Size	Pattern Design	Load Index, Speed Symbol	Additional Marking	Approved Rims (in)	Overall Diameter (mm)	Tyre Width (mm)	Static Loaded Radius (mm)	Rolling Circ. (mm)	Revolutions per km	Revolutions per mile	Minimum Dual Spacing (mm)
295/80R22.5	HKPL TRUCK F	152/148M	-	9.00 , 8.25	1049	299	489	3189	314	505	335
315/70R22.5	HKPL TRUCK F	152/148M	154/150L	9.00 , 8.25	1024	314	472	3109	322	518	335
315/80R22.5	HKPL TRUCK F	154/150M	156/150L	9.00 , 9.75	1081	314	503	3292	304	489	351
385/65R22.5	HKPL TRUCK F	158L	160K	11.75 , 12.25	1088	375	504	3313	302	486	-
295/80R22.5	HAKKA TRUCK 861	152/148M	-	9.00 , 8.25	1050	300	488	3185	314	505	335
315/70R22.5	HAKKA TRUCK 861	152/148M	154/150L	9.00 , 8.25	1025	314	472	3109	322	518	335
315/80R22.5	HAKKA TRUCK 861	154/150M	156/150L	9.00 , 9.75	1079	313	502	3281	305	491	351
385/65R22.5	HAKKA TRUCK 861	158L	160K	11.75 , 12.25	1084	377	501	3293	304	489	-
295/80R22.5	NTR-831	152/148M	-	9.00 , 8.25	1063	295	495	3231	310	498	335
315/70R22.5	NTR-831	152/148M	154/150L	9.00 , 8.25	1032	315	476	3136	319	513	351
315/80R22.5	NTR-831	154/150M	156/150L	9.00 , 9.75	1087	313	505	3304	303	487	351
295/80R22.5	HKPL TRUCK E	152/148M	-	9.00 , 8.25	1064	296	495	3231	310	498	335
315/70R22.5	HKPL TRUCK E	152/148M	154/150L	9.00 , 8.25	1031	314	476	3136	319	513	351
315/80R22.5	HKPL TRUCK E	154/150M	156/150L	9.00 , 9.75	1086	312	503	3292	304	489	351
265/70R19.5	HAKKA TRUCK 844	143/141J	-	7.50 , 6.75, 8.25	872	251	403	2650	377	607	295
275/70R22.5	HAKKA TRUCK 844	148/145L	-	8.25 , 7.50	964	272	448	2930	341	549	311
265/70R19.5	NTR-827	143/141J	-	7.50 , 6.75, 8.25	872	254	403	2649	378	608	295